

(19)



Europäisches Patentamt
European Patent Office
Office européen des brevets

(11) Publication number:

0 061 000
A1

(12)

EUROPEAN PATENT APPLICATION

(21) Application number: 82101275.4

(51) Int. Cl.³: G 06 K 7/10

(22) Date of filing: 19.02.82


(30) Priority: 16.03.81 JP 38158/81

(43) Date of publication of application:
29.09.82 Bulletin 82/39(84) Designated Contracting States:
DE FR GB(71) Applicant: NIPPONDENSO CO., LTD.
1, 1-chome Showa-cho
Kariya-shi Aichi-ken(JP)(72) Inventor: Hara, Masahiro
6-30, Tenno-cho
Kariya-shi Aichi-ken(JP)(72) Inventor: Sakai, Toshiyasu
8, Hamabaura Hitotsugi-cho
Kariya-shi Aichi-ken(JP)(72) Inventor: Okamoto, Atsutoshi
7-21, Aza Iguiba Ohaza Morioka
Higashiura-cho Chita-gun Aichi-ken(JP)(74) Representative: Klingseisen, Franz, Dipl.-Ing. et al,
Dr. F. Zumstein sen. Dr. E. Assmann Dr. R.
Koenigsberger Dr. F. Zumstein jun. Dipl.-Ing. F.
Klingseisen Bräuhausstrasse 4
D-8000 München 2(DE)

(54) Bar code scanner.

(57) A bar code scanner for scanning bar codes having a plurality of parallel bar symbols recorded in different light reflective colors on a record medium. The scanner has a light source, an image sensor comprising a plurality of light responsive elements which are aligned and activated one by one, and diaphragm having an aperture which is longitudinally extending in orthogonal relation with the straight line of the aligned elements.

FIG.2.



EP 0 061 000 A1

BAR CODE SCANNER

BACKGROUND OF THE INVENTION

1 The present invention relates to a bar code scanner for scanning bar codes by an electronically
5 activated image sensor, which is used in such a system that articles of merchandise move together with a record medium (for example, labels or the like) affixed thereto and recorded with the bar codes.

10 In a conventional apparatus for scanning a light reflected from bar codes or contrastive light reflection pattern by an electronically activated image sensor, it is known that an iris diaphragm is provided for projecting enough illuminance on the bar codes so as to clearly image the bar codes on the
15 light responsive elements of the image sensor, and for controlling the focal depth of the bar codes image.

While it is generally arranged that the circular aperture of the iris diaphragm is small so as to prevent the defocus of the image or to increase the
20 focal depth, a luminous intensity reflected from bar codes onto the image sensor is reduced by the small aperture and it is required to employ the light source having a large luminous intensity so as to compensate the reduced luminous intensity.

25 When the aperture of the iris diaphragm is large so as to increase the luminous intensity projecting on the image sensor, the focal depth is reduced and consequently the scanning accuracy is reduced.

1

SUMMARY OF THE INVENTION

5

With a view to overcoming the foregoing deficiencies, it is an object of the invention to increase the focal depth without decreasing the luminous intensity of the light reflected from the bar codes onto the image sensor, and thus provide the bar code scanner with greater scanning accuracy.

BRIEF DESCRIPTION OF THE DRAWINGS

10

FIG. 1 is a schematic view illustrating the general positions for explanation of the optical system according to the invention;

FIG. 2 is a sectional view illustrating the detailed construction of the invention; and,

15

FIGS. 3 - 5 are plan views illustrating the first to third embodiments of diaphragm means in FIG. 2.

In the above drawings, the same reference numerals are used to indicate the same or equivalent parts.

1 DESCRIPTION OF THE PREFERRED EMBODIMENTS

In the optical system according to the present invention, in which the scanned image of bar codes illuminated by the light source is orthogonally
5 imaged on the straight aligned light responsive elements of the image sensor, an aperture of the diaphragm member extending in an orthogonal relation with the elements of image sensor.

The present invention will now be described
10 in greater detail with reference to the illustrated embodiments. Referring first to FIGS. 1 and 2, numeral 1 designates a light source such as a bar-shaped lamp which illuminates bar codes 3a printed on a bar code label 3 through a light collector lens 2 of
15 semi-cylindrical shape. The bar codes 3a comprise a plurality of parallel bar symbols recorded in white and in black which are contrastive colors in light reflectivities, and the bar symbols play as a coding with the colors and the widths thereof. Numeral 4
20 designates a concave reflector mirror for reflecting the reflected light from the bar codes 3a to a specified direction. The light thus reflected by the mirror 4, passing through a convex lens 5 and an aperture 6a of diaphragm member 6, is received by an
25 image sensor 7. As the image sensor 7, a one-directional image sensor is employed for converting the scanned image on a read-in line 7a to an electric signal by means of an electronically scanning operation.

- 4 -

1 As shown in FIG. 3, the aperture 6a of the
diaphragm 6 has a shape of rectangle longitudinally
extending in direction orthogonal to the read-in line
7a. A one-dot chain line of optical system in FIG. 1
5 shows a ray in the scanner according to the present
invention. Numeral 8 designates electronically
controlled circuits for activating the image sensor 7
and processing electric signals therefrom so as to
convert to the desired digital signals corresponding to
10 the bar codes 3a. Numeral 10 designates an outer
casing made of synthetic resin which may be handled by
the operator. Numeral 11 designates an inner casing
for supporting the concave reflector mirror 4, the lens
5, the diaphragm member 6, the image sensor 7, the
15 light source 1, the collector lens 2, and a reflector
mirror 12 reflecting the light projected by the light
source 1 onto the bar code label 3.

In the abovementioned construction, the
apparatus is operated in the following manner. When
20 the scanning apparatus is provided at the position as
shown in FIG. 2, the light projected by the bar-shaped
lamp 1 is converged by the collector lens 2, and
illuminates the bar code label 3. Since the bar
symbols of the bar codes 3a are recorded in white and
25 in black which are contrastive colors in light
reflectivity, the reflected light has corresponding
light densities. The reflected light, passing via the
concave reflector mirror 4, the lens 5 and the aperture
6a of the diaphragm means 6, is received by the image

- 5 -

1 sensor 7 on the read-in line 7a thereof. The image
sensor 7 which is activated by the electronically
controlled circuits 8 converts the scanned image to
electric signals, and the circuits 8 produce the
5 desired digitally coded signals corresponding to the
above electric signals.

Since the longitudinal axis of the aperture
6a of the diaphragm means 6 is positioned in direction
orthogonal to the straight image-in line 7a of the
10 read sensor 7, the focal depth of the axis X as shown
in FIG. 1 (i.e. the width of each bar symbols of the
bar codes 3a) becomes wide in response to the decrease
of width of the aperture 6a. Furthermore, since the
enough luminous intensity is obtained owing to the
15 longitudinal length of the aperture 6a in comparison
with the conventional iris diaphragm, the precise
scanning is assured and it is not required to employ
the light source having large luminous intensity.
Still furthermore, since the light reflected by the
20 axis Y of the bar code label 3 is converged on the
image sensor 7 by the concave collector mirror 4, it
is also seen that even the comparatively small
luminous intensity is satisfactory without decreasing
the focal depth.

25 The aperture 6a of the diaphragm means may
be further modified as shown in FIGS. 4 and 5. In
FIGS. 4 and 5, the diaphragm means 6 has an elliptical
aperture 6b or a rhombus aperture 6c, the longitudinal

- 6 -

1 axis of which is extending in parallel with the
reflected light of the longitudinal axis of the bar
codes 3a.

5 In place of the lens 5, a concave mirror may
be provided for imaging on the image sensor 7.

While the diaphragm means 6 is separate from
the lens 5 in the above description, an opaque tape or
paint may be applied on the surface of the lens 5 so
as to form the diaphragm means 6.

10 The present invention is not limited to the
embodiments described hereinabove but may be modified
or altered in many ways without departing from the
spirit of the invention.

- 1 -

What is claimed is:

1. In a system for scanning bar codes having a plurality of parallel bar symbols recorded in different light reflective colors, a bar code scanner comprising:

 a casing;

 a light source supported within said casing and illuminating said bar symbols;

 an image sensor supported within said casing and being electronically activated one by one to convert reflected light applied from said parallel bar symbols into responsive electric signals, the longitudinal axis of said bar symbols being reflected orthogonally onto the straight read-in line of said image sensor; and

 diaphragm member supported within said casing at a portion between said bar symbols and said image sensor and having an aperture, the longitudinal axis of said aperture extending in orthogonal relation with said straight read-in line of said image sensor.

2. A bar code scanner according to Claim 1, wherein said aperture has a rectangular shape.

3. A bar code scanner according to Claim 1, wherein said aperture has an elliptical shape.

4. A bar code scanner according to Claim 1, wherein said aperture has a rhombus shape.

5. A bar code scanner according to Claim 1 further comprising a lens supported within said casing at a position between said bar symbols and said image sensor and focusing the light reflected from said bar symbols onto said image sensor.

6. A bar code scanner according to Claim 5, wherein said diaphragm member is formed directly on the surface of said lens.

7. A bar code scanner according to anyone of Claims 1 or 5 further comprising a lens supported within said casing at a position between said light source and said bar symbols and converging the light projected by said light source onto said bar symbols.

8. In a system for scanning bar codes having a plurality of parallel bar symbols recorded in contrastive light reflection colors, a bar code scanner comprising:

a casing;

a light source supported within said casing and illuminating said bar symbols;

an image sensor supported within said casing and being electronically activated one by one to convert reflected light applied from said parallel bar

symbols into responsive electric signals, the longitudinal axis of said bar symbols being reflected orthogonally onto the straight read-in line of said image sensor;

diaphragm member supported within said casing at a portion between said bar symbols and said image sensor and having an aperture, the longitudinal axis of said aperture extending in orthogonal relation with said straight read-in line of said image sensor;

a lens supported within said casing at a position between said bar symbols and said image sensor and focusing the light reflected from said bar symbols onto said image sensor;

a lens supported within said casing at a position between said light source and said bar symbols and converging the light projected by said light source onto said bar symbols;

a first reflector mirror supported within said casing and reflecting the light reflected from said bar symbols onto said image sensor; and,

a second reflector mirror supported within said casing and reflecting the light projected by said light source onto said bar symbols.

FIG. 1.




FIG. 2.




FIG. 3.




FIG. 4.





FIG. 5.





European Patent
Office

EUROPEAN SEARCH REPORT

0061000

Application number

EP 82 10 1275

DOCUMENTS CONSIDERED TO BE RELEVANT

Category	Citation of document with indication, where appropriate, of relevant passages	Relevant to claim	CLASSIFICATION OF THE APPLICATION (Int. Cl. 3)
Y	FR-A-2 212 967 (BERTIN) *Figures 1-9; from page 2, line 26 to page 5, line 8*	1-7	G 06 K 7/10
Y	--- US-A-3 553 468 (DENCH) *Figures 1-3; from column 1, line 61 to column 2, line 61*	1-7	
Y	--- US-A-3 684 866 (JONES) *The whole document*	4	
Y	--- US-A-3 351 765 (MALONE et al.) *Figures 1-4; from column 3, line 22 to column 5, line 11*	3	

The present search report has been drawn up for all claims			TECHNICAL FIELDS SEARCHED (Int. Cl. 3)
			G 06 K 7/10
Place of search THE HAGUE		Date of completion of the search 29-06-1982	Examiner FORLEN G.A.

CATEGORY OF CITED DOCUMENTS

X : particularly relevant if taken alone
Y : particularly relevant if combined with another document of the same category
A : technological background
O : non-written disclosure
P : intermediate document

T : theory or principle underlying the invention
E : earlier patent document, but published on, or after the filing date
D : document cited in the application
L : document cited for other reasons
& : member of the same patent family, corresponding document